

General Disclaimer

One or more of the Following Statements may affect this Document

- This document has been reproduced from the best copy furnished by the organizational source. It is being released in the interest of making available as much information as possible.
- This document may contain data, which exceeds the sheet parameters. It was furnished in this condition by the organizational source and is the best copy available.
- This document may contain tone-on-tone or color graphs, charts and/or pictures, which have been reproduced in black and white.
- This document is paginated as submitted by the original source.
- Portions of this document are not fully legible due to the historical nature of some of the material. However, it is the best reproduction available from the original submission.

E83-10423

SOF

AN-A46: Landsat Scene-to-Scene Registration Assessment

TM-85420

Principle Investigator: James E. Anderson
NASA/NSTL/Earth Resources Laboratory
Code HA20/Building 1100
NSTL, Mississippi 39529



Quarterly Report for Period: 22 June 1983 - 21 August 1983

Objectives:

- to evaluate the scene-to-scene registration performance of the Landsat-4 MSS relative to previous MSS systems
- to evaluate the scene-to-scene registration performance of the Landsat-4 Thematic Mapper (TM).

Activity this Quarter:


- A summary report dealing with the use of Landsat-4 MSS data in temporal data sets has been printed as NASA/NSTL/ERL internal report #222 (a copy enclosed). The report has also been submitted to Photogrammetric Engineering and Remote Sensing for possible future publication.
- Reprocessed 16 September 1983 data set of the New Orleans and Mississippi Gulf Coast area received. Initial analysis of the radiometric/geometric quality commenced.

Activity Anticipated Next Quarter:

- Receipt of second TM data set (perhaps a reprocessed December 1983 scene) which would permit scene-to-scene registration work to begin

Problems Encountered

- Lack of a second TM data set will preclude scene-to-scene work from taking place.



(E83-10423) THE USE OF LANDSAT-4 MSS
DIGITAL DATA IN TEMPORAL DATA SETS AND THE
EVALUATION OF SCENE-TO-SCENE REGISTRATION
ACCURACY Quarterly Report, 22 Jun. -
21 Aug. 1983 (NASA) 18 p HC AC2/MF A01

N83-35462

Unclas
G3/43 00423

SA

THE USE OF LANDSAT-4 MSS DIGITAL DATA IN TEMPORAL DATA SETS AND
THE EVALUATION OF SCENE-TO-SCENE REGISTRATION ACCURACY

"Made available under NASA sponsorship
in the interest of early and wide dis-
semination of Earth Resources Survey
Program information and without liability
for any use made thereof."

E83-10423

~~83-10423~~

TM-85420

by

James E. Anderson

July, 1983

Earth Resources Laboratory.
National Space Technology Laboratories
NSTL, MS 39529

Report No. 222




TABLE OF CONTENTS

	<u>Page</u>
1. ABSTRACT.	1
2. INTRODUCTION.	1
3. TECHNICAL APPROACH.	3
A. Generation of Temporal Data Sets.	3
B. Registration Evaluation Methodology	5
C. Data Sources.	9
4. ANALYSIS AND RESULTS.	10
5. CONCLUSIONS	12
REFERENCES.	13

LIST OF TABLES

<u>TABLE</u>	<u>TITLE</u>	<u>PAGE</u>
1	Data Sources for the Temporal Registration Investigation	9
2	Results Obtained for the Registration of Three Scenes of Landsat P-Format MSS Data to a Common Data Base Set	10

THE USE OF LANDSAT-4 MSS DIGITAL DATA IN TEMPORAL DATA SETS AND THE EVALUATION OF SCENE-TO-SCENE REGISTRATION ACCURACY

ABSTRACT

The MSS sensor on Landsat-4 is, in certain performance aspects, different from those on Landsats 1 through 3. These differences have created some concern in the NASA research community as to whether individual data sets can be registered accurately enough to produce acceptable data for multitemporal data analysis. This study examines the use of Landsat-4 MSS digital data in temporal data sets, and presents a method for estimating temporal registration accuracy based on the use of an X-Y digitizer and grey tone electrostatic plots. Results obtained indicate that the RMS temporal registration errors were not significantly different between the temporal data sets generated using Landsat-4 and Landsat-2 data (33.35 meters) and the temporal data set constructed from two Landsat-2 data sets (33.61 meters). A derivation of the model used to evaluate the temporal registration is included.

INTRODUCTION

The purpose of multitemporal registration, using data from a sensor such as the Landsat Multispectral Scanner (MSS), is to produce a single multichannel data set from two or more individual multichannel data sets separated in time. The data from one date are used as a base and all other data are fitted or mapped onto them. It is generally accepted

that by producing such a temporal data set researchers can capitalize on changes which occur (or do not occur) over the time frame encompassed, thus gaining an added dimension that will lead to improvements in the utility of the data being examined. For example, studies by Badhwar, et al. (1982), and Hay, et al. (1982), describe the use of temporal agronomic crop signatures which characterize Landsat MSS data values as functions of crop phenology or growth state. Such temporal analyses have produced results which are significantly better than those obtained with single-date data sets. Mergerson (1981) points out that as a result of better discrimination, multirate data sets produce improved crop area estimates. Representative research in the application of multitemporal data for investigations in Forestry (Lee, 1980), Hydrology (Saito, et al. 1982), Ice and Snow Field studies (Dey, 1980), Wetlands and Coastal Processes (Lim, et al. 1980), Land Cover Dynamics (Byrne, et al. 1980), and Land Use Mapping/Natural Resources Inventories (Lichtenegger and Seidel, 1981) have demonstrated the widespread interdisciplinary utility of temporal data.

Results obtained from the use of temporal data are related to the degree to which two or more data sets can be registered one to another; the better the registration, the better the expected results ceteris paribus. Registration errors can arise from numerous sources. Of particular interest to this study are registration errors which might be caused by differences in the sensor being used.

By design, sensor or platform differences between the first three Landsat satellites were insignificant and thus MSS data registration errors induced by satellite system differences were minimal. However,

the Landsat-4 MSS is in at least two respects different from its predecessors. First, the scan angle is wider (14.9 degrees vs. 11.6 degrees), and second, the instantaneous field of view (ground resolvable area) is slightly different (82.7 x 57 meters vs. 79 x 56 meters). Software at the ground processing facility of the NASA Goddard Space Flight Center (GSFC) has been designed to produce "standardized" P-format digital data from the raw Landsat-4 MSS data. However, there has been some concern expressed about whether the registration of temporal data sets, which include Landsat-4 MSS data, has been adversely affected (NASA, 1981). GSFC therefore encouraged research in constructing temporal data from Landsat-4 MSS and Landsat 1 through 3 MSS data, through the NASA-sponsored Landsat-D Image Data Quality Analysis (LIDQUA) Program, to verify continuity of this feature. As its commitment to the LIDQUA Program, NASA's Earth Resources Laboratory located at the National Space Technology Laboratories (NASA/NSTL/ERL) has conducted temporal registration assessment research using Landsat-4 MSS data.

TECHNICAL APPROACH

Generation of Temporal Data Sets

The procedures for generating temporal data sets are well documented in the literature (see especially Bryant, 1982 for a summary). However, a brief discussion of the specific technique as implemented at NASA/NSTL/ERL is warranted.

The first step in producing a temporal data set is to choose a "base" and a "map" data set. In the context of this paper, base data is used "as is", i.e., it furnishes the scan line and pixel coordinate

system onto which the map data will be fitted. The map data set(s) is therefore the set which is contorted (stretched/shrunk) to overlay the base data set. After designating the base and map data sets, six to ten uniformly distributed points which represent unambiguous scene locations are located in both data sets. The scan line/pixel coordinates of the points (for both data sets) are used to compute an initial set of mapping equations. Such equations define the fundamental relationship between points located in the map data set and identical locations in the base data set.

Based on the initial mapping equations, auto-correlation software is used to locate 100 to 200 additional points which represent common geographic locations in both data sets. Initially, points are located in the base data set, and a window of data centered on each point is extracted. For each such point in the base data set, the initial mapping equations are used to calculate an expected location in the map data set. A sliding window the same size as used in the base data is then moved around the expected location in the map data set, moving one pixel or scan line at a time. Each movement results in the extraction of a slightly different digital count data sample and the correlation of each map data sample with the base data sample is computed. The pixel located at the center of the window (in the map data) with the highest correlation to the corresponding window of base data is retained as the most probable location for a matching point. This procedure continues until all points located in the base data set have been processed.

Points located by the auto-correlation software are manually edited, since some points may not adequately depict the relationship between the

base and map data sets. Those which are found to be questionable are deleted, and a final set of mapping equations is generated along with an RMS registration error that is computed using the retained control points. Temporal registration is then accomplished using a piecewise linear fit with bilinear resampling.

Registration Evaluation Methodology

In order to evaluate the level of temporal registration success, a technique has been developed at NASA/NSTL/ERL which relies on the use of an X-Y digitizer and electrostatic grey-level plots. Numerous randomly located subscene areas (approximately 512 scan lines by 512 pixels in size) are located in the newly constructed temporal data set. Three digital count-to-grey level plots are generated for each subscene area chosen, one plot for each of two channels of the original base data, and one plot for a single channel of the mapped data set after the map data set has been resampled. The channels selected are typically MSS channel 5 (0.7 to 0.8 micron wavelength region) and MSS channel 7 (0.8 to 1.1 micron wavelength region) for the base data, and MSS channel 5 for the mapped data. Since the plots are generated from the temporal data set, scan line/pixel coordinates are identical for all plots of a specific subscene area, i.e., the scan lines/pixels of the mapped data are now in terms of base data coordinates, since the remapping has already taken place.

For each subscene area used, the corresponding plots are simultaneously mounted on the table of an X-Y digitizer. After initializing the digitizer to the plots, overlay assessment (OA) points,

which are unambiguously identifiable on all three plots, are located and their scan line/pixel coordinates are recorded using the digitizer. For each OA point located, three sets of scan line/pixel coordinates are generated, since three plots are used. All coordinates are stored by sample number for subsequent use.

The digitized coordinates are then processed by statistical analysis software, which computes the statistics defining the RMS error associated with the temporal data set examined. The software is unique in that it computes total error, errors associated with human location of OA points, and an estimate of actual temporal registration error (which can be thought of as total error minus the human error). The following discussion is an amplification of the analysis model originally designed by Seyfarth and Cook (1981).

The model employed assumes that for each point sampled:

$$X_{b1i} = X_i + E_{b1i}$$

where X_{b1i} is the pixel coordinate for the i^{th} OA test point in the first channel of the base data set used, X_i is the theoretically true location of the i^{th} test point, and E_{b1i} is the human error associated with selecting that test point. This assumption applies to the second base channel used as well as to the mapped channel and yields:

$$X_{b2i} = X_i + E_{b2i}, \text{ and}$$

$$X_{mi} = X_i + E_{mi} + \alpha_i$$

where X_{b2i} , X_{mi} are the X coordinates for the i^{th} point from the second base channel used and the mapped data channel respectively, E_{b2i} , E_{mi}

ORIGINAL PAGE IS
OF POOR QUALITY

represent the human error contribution for the i^{th} point selected from the second base channel used and the mapped data channel respectively, and a_i is the actual misregistration at the i^{th} point. It is also assumed that E_{b1} , F_{b2} , E_m and a are all independent random variables, normally distributed with means of zero and variances σ_{xb1}^2 , σ_{xb2}^2 , σ_{xm}^2 , and σ_a^2 , and that σ_{xb1}^2 , σ_{xb2}^2 , and σ_{xm}^2 are all equal to σ_{xh}^2 which is associated with the human error component. (All through this discussion similar formulae could be derived for the scan line (Y) component, but for the sake of brevity such derivations will not be explicitly made.)

Since X_{b1i} and X_{b2i} represent coordinates of the same point chosen from two channels of the base data set, consider:

$$\sum_{i=1}^n \frac{(X_{b1i} - X_{b2i})^2}{n}$$

which can be expanded to yield:

$$\sum_{i=1}^n \frac{(X_i + F_{b1i} - X_i - E_{b2i})^2}{n}$$

The assumption of independence leads to:

$$\begin{aligned} & \sum_{i=1}^n \frac{F_{b1i}^2}{n} + \sum_{i=1}^n \frac{E_{b2i}^2}{n} \\ &= \sigma_{xb1}^2 + \sigma_{xb2}^2 \\ &= 2 \sigma_{xh}^2 \end{aligned}$$

So an estimate for the human error component is:

$$\sigma_{xh}^2 = \frac{1}{2} \sum_{i=1}^n \frac{(X_{b1i} - X_{b2i})^2}{n}$$

The coordinate derived from the map channel (X_{m1}) is used as follows.

Consider the difference between the X_{m1} and the average of X_{b1i} and

X_{b2i} :

$$\begin{aligned} & \sum_{i=1}^n \left[\frac{X_{m1} - (X_{b1i} + X_{b2i})}{2} \right]^2 \\ &= \frac{1}{n} \sum_{i=1}^n \left[X_i + E_{m1} + a_i - \frac{(X_i + E_{b1i} + X_i + E_{b2i})}{2} \right]^2 \\ &= \frac{1}{n} \sum_{i=1}^n \left[E_{m1} + a_i - \frac{E_{b1i}}{2} - \frac{E_{b2i}}{2} \right]^2 \end{aligned}$$

The assumption of independence yields:

$$\sum_{i=1}^n \frac{E_{m1}^2}{n} + \sum_{i=1}^n \frac{a_i^2}{n} + \frac{1}{4} \sum_{i=1}^n \frac{E_{b1i}^2}{n} + \frac{1}{4} \sum_{i=1}^n \frac{E_{b2i}^2}{n}$$

which is identical to:

$$\sigma_{xh}^2 + \sigma_a^2 + \frac{1}{2} \sigma_{xh}^2$$

After replacing σ_{xh}^2 with its earlier derived equivalent and rearranging terms we get:

ORIGINAL PAGE IS
OF POOR QUALITY

$$\sigma_a^2 = \frac{\sum_{i=1}^n x_{mi} - (x_{b1i} - x_{b2i})^2}{2n} - \frac{3}{4} \sum_{i=1}^n \frac{(x_{b1i} - x_{b2i})}{n}$$

In order to obtain the error in terms of meters (since σ_{xh} and σ_a are in terms of pixels)

$$\sigma_{x \text{ meters}} = 57\sigma_a \quad \text{for P-format Landsat MSS data.}$$

As previously mentioned, a similar formula could be derived for σ_y meters. Thus, the total RMS error (in meters) would be:

$$\sigma_{\text{model}} = \sqrt{\sigma_{x \text{ meters}}^2 + \sigma_{y \text{ meters}}^2}$$

It is thus possible to obtain estimates of the actual misregistration error in temporal data sets.

Data Sources

Four P-Format MSS data sets were used in this study as defined in Table 1. All scenes included the New Orleans, Louisiana, metropolitan area (Landsat-4 worldwide reference system Path 22, Row 39) as well as portions of the Mississippi Gulf Coast. A diversity of land covers/land use was present including cropland/pasture, dryland, forest, forested wetlands, marsh, water bodies, small towns, rivers, etc.

Landsat			
MSS	Date	Scene ID	Comments
2	Sept 1980	22063-15500	Served as the base data set for the study
2	Feb 1981	22225-15485	
4	Sept 1982	40062-15591	Scene produced using pre-launch software parameters at NASA/Goddard Space Flight Center
4	Mar 1983	40238-16010	Modified software parameters used

Table 1. Data Sources for the Temporal Registration Investigation.

Landsat-2 MSS data for 1980 served as the base data set throughout the study, as they were already in house. All other data were used as map data sets, and were independently registered to the 1980 data set.

ANALYSIS AND RESULTS

Actual analysis began with the temporal registration of the 1981 Landsat-2 data set to the 1980 Landsat-2 data set. The results obtained (Table 2) were typical of temporal registrations obtained in the past at NASA/NSTL/ERL using Landsat 1, 2, or 3 data sets. Subsequent analysis of the errors on an OA point-by-OA point basis showed no trends in the registration errors in terms of direction of error or magnitude. Thus, a particularly "uniform" fit was achieved.

COMPONENT ERROR	LANDSAT-2 (1981)	LANDSAT-4 (1982)	LANDSAT-4 (1983)
Pixel Error	20.42 meters	40.32 meters	20.04 meters
Scan line Error	26.70 meters	26.95 meters	26.65 meters
Model RMS Error	33.61 meters(74)*	48.50 meters(65)*	33.35 meters(72)*

Table 2. Results Obtained for the Registration of Three Scenes of Landsat P-Format MSS Data to a Common Base Data Set.

*Values enclosed in parentheses represent the number of points used to generate the corresponding statistic.

The 1982 Landsat-4 MSS data set was received in January 1983, and an independent temporal registration was produced. The results (Table 2) indicated a substantial pixel component error (almost twice the error obtained in the Landsat-2 to Landsat-2 registration). The model error (estimate of the actual misregistration) also demonstrated a

considerable degeneration, undoubtedly the result of the large pixel error. When examined on an OA point-by-OA point basis however, a sinusoidal pattern was observed when the magnitude of the pixel errors was plotted versus pixel location. Since the position of the MSS scan mirror is directly related to the pixel location, this result suggested that the coefficients used to model the scan mirror motion were not correct. No detectable pattern was noted for scan line errors.

In late January 1983, just before the MSS system onboard Landsat-4 was turned over to NOAA, corrections were made to the scan mirror coefficients used in the Goddard Space Flight Center's ground processing software associated with the Landsat-4 MSS system. The impact of this change can be seen in Table 2. The 1983 data set was collected and processed after the new coefficients were incorporated into the software. As can be seen, the pixel component error has been reduced considerably and is now at the same level as the Landsat-2 only temporal registration. The scan line component seems to have been unaffected, and remains nearly constant for all of the temporal registrations produced, showing no discernible trends in either magnitude or direction.

In order to determine the significance of the changes noted, F-tests were conducted on the model RMS errors. The results indicated that at the 10 percent level of confidence, the temporal registration using 1982 Landsat-4 MSS data (erroneous scan mirror coefficients) was significantly different from each of the two other temporal registrations. The results based on the use of the 1983 Landsat-4 MSS data (corrected coefficients) were not significantly different from those obtained using the 1981 Landsat-2 MSS data.

CONCLUSIONS

It has been demonstrated that temporal registration of Landsat-4 MSS P-format digital data with historical data obtained by Landsat-2 can be performed to a degree of precision equal to that obtained when using Landsat-2 data as both the base and map data sets. Landsat-4 MSS data collected between July 1982 and February 1983 should be used with caution, since scan mirror motion coefficients were not optimum and use of the data may produce less than desirable results.

REFERENCES

- Badhwar, G.D., J.G. Carnes, and W.W. Austin. 1982. Use of Landsat-derived Temporal Profiles for Corn Soybean Feature Extraction and Classification. Remote Sensing of the Environment, Vol. 12, No. 1, pp. 57-79.
- Bryant, N.A. 1982. Proceedings of the NASA Workshop on registration and rectification. Held at the Jet Propulsion Laboratory, Pasadena, California. National Aeronautics and Space Administration, Washington, D.C. 535 p.
- Byrne, G.F., P.F. Crapper, and K.K. Mayo. 1980. Monitoring Land Cover Change by Principal Component Analysis of Multitemporal Landsat Data. Remote Sensing of the Environment, Vol. 10, No. 3, pp. 175-184.
- Dey, B. 1980. Orbital Sensing of Mackenzie Bay (Canada) Ice Dynamics. Arctic Montreal, Vol. 33, No. 2, pp. 280-291.
- Hay, C.M., L.H. Beck, and E.J. Sheffner. 1982. Use of vegetation indicators for crop group stratification and efficient full frame analysis. In Proceedings of the International Symposium on Remote Sensing of Environment, First Thematic Conference. (Remote Sensing of Arid and Semi-arid Lands) January 19-25, 1982, Cairo, Egypt, pp. 737-747.
- Lee, Y.J. 1980. Application of Temporal Landsat Forest Digital Data to Yukon Information-Retrieval System Using Aries. Forestry Chronicle, Vol. 56, No. 1, pp. 31.
- Lichtenegger, J. and K. Seidel. 1981. Detailed land use classification based on multitemporal Landsat-MSS data. In Proceedings of the Fifteenth International Symposium on Remote Sensing of Environment, May 11-15, 1981. Ann Arbor, Michigan. Vol. II, pp. 997-1005.
- Lim, J.B.R., E.S. Elefan, and R.S. Jara. 1980. Coastal change assessment of the nuclear power plant site in Bataan, Philippines using Landsat temporal data. In Proceedings of the Fourteenth International Symposium on Remote Sensing of Environment, April 23-30, 1980, San Jose, Costa Rica. pp. 819-832.
- Mergerson, J.W. 1981. Crop Area Estimates Using Ground-Gathered and Landsat Data: A Multitemporal Approach: Missouri 1979. U.S. Dept. of Agriculture, Economics and Statistics Service Staff Report, AGESS810223, Washington, D.C. 27 p.
- NASA, 1981. Applications Notice for Participation in the Landsat-D Image and Data Quality Analysis Program. National Aeronautics and Space Administration, Goddard Space Flight Center, AN; GSFC-81-A, Greenbelt, Maryland.

Saito, S., Y. Sasaki, T. Muneyama, and J. Iisaka. 1982. Temporal Analysis of suspended solid in Tokoyo Bay by Landsat data. In: 10th Symposium on the study of land transformation processes, twenty-fourth plenary meeting. COSPAR Comittee on Space Research. Held in Ottawa, Canada May 16-June 2, 1982.

Seyfarth, B.R. and P.W. Cook. 1981. An Analysis of Landsat MSS Scene-to-Scene Registration Accuracy. NASA National Space Technology Laboratories Report No. 198, 10 p.